

618195.000

Technical Data Light source: LED Wattage: 12W

Voltage: 220-240VAC Nominal luminous flux: 970lm Beam angle: 16°, spot

Color temperature: 4000K, neutral white

Color Rendering Index: 90

Technical Chracteristics

Protection degree: IP20 (En60598) Insulation class: Class I (En60598)

Product Description

Housing and bracket: cast aluminium, powder-coated, Black. 0°- 270°tilt.


Bracket rotatable through 360° on 3-circuit adapter.

3-circuit adapter: plastic.

Including electronic control, dimmable with potentiomen ter for brightness control 0-100%.

Replaceable LED module: high-power LEDs on metal-core PCB, Collimating lens made of optical polymer. Front cover: plastic.

Weight: 0.45kg













Dimension



Lighting Distribution Planning Data



	2			h=	2.15m	
	1					
	0	50	20/5.0 20/5.0			
	1					
[m]	2	1 (0	1 2	2 3	3

E(lx)H(m) D(m) 7916 1.0 0.26

2.0 1979 0.52 3.0 0.78 880 4.0 1.04 495 317 5.0 1.30

ηLOR=80% UGR=12.3

E[lx]	100lx	500lx	
a[m²] 100	n=13	n=65	

All data, images, and specifications are for reference only and may be changed due to product improvement without prior notice.



3 circuit track



Surface mounted universal mono track point



Recessed mounted universal mono track point



Replaceable accessories principal lens