


## 618196.000

Technical Data Light source: LED Wattage: 12W Voltage: 220-240VAC Nominal luminous flux: 970lm Beam angle: 16°, spot Color temperature: 4000K, neutral white Color Rendering Index: 90

**Technical Chracteristics** Protection degree: IP20 (En60598) Insulation class: Class I (En60598)


## Product Description


Housing and bracket: cast aluminium, powder-coated, Black. 0°- 270°tilt. Bracket rotatable through 360° on 3-circuit adapter. 3-circuit adapter: plastic. Including electronic control, DALI Plug & Play. Replaceable LED module: high-power LEDs on metal-core PCB, Collimating lens made of optical polymer. Front cover: plastic. Weight: 0.45kg




☆ C € ♥

## Dimension





Lighting Distribution Planning Data



D(m)	E(lx)
0.26	7916
0.52	1979
0.78	880
1.04	495
1.30	317

H(m)

1.0

2.0

3.0

E[lx]	100lx	500lx
a[m² ] 100	n=13	n=65

All data, images, and specifications are for reference only and may be changed due to product improvement

without prior notice.





2 1

0

1 2

[m]

1 0 1

> Surface mounted universal mono track point

2 3



Recessed mounted universal mono track point

More details at www.akzu.com/618196 QQ

Replaceable accessories principal lens