

618198.000

Technical Data Light source: LED

Wattage: 12W Voltage: 220-240VAC Nominal luminous flux: 970lm Beam angle: 29°, flood

Color temperature: 4000K, neutral white

Color Rendering Index: 90

Technical Chracteristics

Protection degree: IP20 (En60598) Insulation class: Class I (En60598)

Product Description


Housing and bracket: cast aluminium, powder-coated, Black. 0°- 270°tilt.

Bracket rotatable through 360° on 3-circuit adapter. 3-circuit adapter: plastic.

Including electronic control, dimmable with potentiomen ter for brightness control 0-100%.

Replaceable LED module: high-power LEDs on metal-core PCB, Collimating lens made of optical polymer. Front cover: plastic.

Weight: 0.45kg













Dimension



Lighting Distribution Planning Data



H(m)	D(m)	E(lx)
1.0 2.0 3.0 4.0 5.0	0.51 1.02 1.53 2.04 2.55	3104 776 345 194 124

h=2.15m 0 3 2 [m]

ηLOR=80% UGR=13.9

E[lx]	100lx	500lx
a[m²] 100	n=13	n=65

All data, images, and specifications are for reference only and may be changed due to product improvement without prior notice.



3 circuit track



Surface mounted universal mono track point



Recessed mounted universal mono track point



Replaceable accessories principal lens