

## 618201.000

Technical Data Light source: LED Wattage: 12W

Voltage: 220-240VAC Nominal luminous flux: 970lm Beam angle: 29°, flood

Color temperature: 4000K, neutral white

Color Rendering Index: 90

## Technical Chracteristics

Protection degree: IP20 (En60598) Insulation class: Class I (En60598)

# Product Description


Housing and bracket: cast aluminium, powder-coated, Black. 0°- 270°tilt.

Bracket rotatable through 360° on 3-circuit adapter.

3-circuit adapter: plastic.

Including electronic control, DALI Plug & Play. Replaceable LED module: high-power LEDs on metal-core PCB, Collimating lens made of optical polymer.

Front cover: plastic. Weight: 0.45kg













### Dimension





	2			h=	I =2.15m I	
	2					
	1					
	0			<b>)</b> —		
	1	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	20/1 58	1		
	1		<b>=</b> 2.0 =			
	2					
[m]		1 (	0 -	1 2	2 3	3

H(m)	D(m)	E(Ix)
1.0	0.51	3104
3.0	1.02 1.53	776 345
4.0	2.04	194
5.0	2.55	124

 $\eta$ LOR=80% . UGR=13.9

E[lx]	100lx	500lx
a[m²] 100	n=13	n=65

All data, images, and specifications are for reference only and may be changed due to product improvement without prior notice.



3 circuit track



Surface mounted universal mono track point



Recessed mounted universal mono track point



Replaceable accessories principal lens