

618205.000

Technical Data Light source: LED Wattage: 12W

Voltage: 220-240VAC Nominal luminous flux: 970lm Beam angle: 47°, broad flood Color temperature: 4000K, neutral white

Color Rendering Index: 90

Technical Chracteristics

Protection degree: IP20 (En60598) Insulation class: Class I (En60598)

Product Description


Housing and bracket: cast aluminium, powder-coated, Black. 0°- 270°tilt.

Bracket rotatable through 360° on 3-circuit adapter.

3-circuit adapter: plastic.

Including electronic control, DALI Plug & Play. Replaceable LED module: high-power LEDs on metal-core PCB, Collimating lens made of optical polymer.

Front cover: plastic. Weight: 0.45kg











Dimension



Lighting Distribution Planning Data



H(m)	D(m)	E(lx)
1.0	0.88	1033
2.0	1.76	258
3.0	2.65	115
4.0	3.53	65
5.0	4.41	41

h=2.15m 0 2 3 [m]

ηLOR=80% UGR=13.0

E[lx]	100lx	500lx
a[m²] 100	n=13	n=65

All data, images, and specifications are for reference only and may be changed due to product improvement without prior notice.



3 circuit track



Surface mounted universal mono track point



Recessed mounted universal mono track point



Replaceable accessories principal lens