

## 618320.000

Technical Data Light source: LED

Wattage: 9W Voltage: 220-240VAC Nominal luminous flux: 720lm Beam angle: 47°, broad flood Color temperature: 4000K, neutral white

Color Rendering Index: 90

Technical Chracteristics

Protection degree: IP20 (En60598) Insulation class: Class I (En60598)

## **Product Description**


Housing and bracket: cast aluminium, powder-coated, Black. 0°- 270°tilt.

Bracket rotatable through 360° on 3-circuit adapter. 3-circuit adapter: plastic.

Including electronic control, dimmable with potentiomen ter for brightness control 0-100%.

Replaceable LED module: high-power LEDs on metal-core PCB, Collimating lens made of optical polymer. Front cover: plastic.

Weight: 0.45kg














## Dimension



## Lighting Distribution Planning Data



0cc		1	
Τ	h-	2.15m	
L	111-	2.13111	
V	\		_



H(m) D(m) E(lx)

1.0	0.88	943
1.5	1.32	419
2.0	1.76	235
2.5	2.20	150
3.0	2.65	104

ηLOR=80% UGR=13.0

E[lx]	100lx	500lx
a[m²] 100	n=18	n=87

All data, images, and specifications are for reference only and may be changed due to product improvement without prior notice.



3 circuit track



Surface mounted universal mono track point



Recessed mounted universal mono track point



Replaceable accessories principal lens