

#### 618884.000

Technical Data Light source: LED Wattage: 12W

Voltage: 220-240VAC Nominal luminous flux: 900lm Beam angle: 16°, spot

Color temperature: 3000K, warm white

Color Rendering Index: 95

### Technical Chracteristics

Protection degree: IP20 (En60598) Insulation class: Class I (En60598)

# Product Description


Housing and bracket: cast aluminium, powder-coated, Black. 0°- 270°tilt.

Bracket rotatable through 360° on 3-circuit adapter.

3-circuit adapter: plastic.

Including electronic control, DALI Plug & Play. Replaceable LED module: high-power LEDs on metal-core PCB, Collimating lens made of optical polymer.

Front cover: plastic. Weight: 0.45kg











#### Dimension




# Lighting Distribution Planning Data



1.0	0.26	6937
2.0	0.52	1734
3.0	0.78	771
4.0	1.04	434
5.0	1.30	277

D(m)

E(lx)



ηLOR=80% UGR=10.6

H(m)

E[lx]	100lx	500lx
a[m²] 100	n=15	n=74

All data, images, and specifications are for reference only and may be changed due to product improvement without prior notice.



3 circuit track



Surface mounted universal mono track point



Recessed mounted universal mono track point



Replaceable accessories principal lens