

618887.000

Technical Data Light source: LED Wattage: 12W Voltage: 220-240VAC Nominal luminous flux: 900lm Beam angle: 29°, flood

Color temperature: 3000K, warm white

Color Rendering Index: 95

Technical Chracteristics

Protection degree: IP20 (En60598) Insulation class: Class I (En60598)

Product Description


Housing and bracket: cast aluminium, powder-coated, Black. 0°- 270°tilt.

Bracket rotatable through 360° on 3-circuit adapter.

3-circuit adapter: plastic.

Including electronic control, DALI Plug & Play. Replaceable LED module: high-power LEDs on metal-core PCB, Collimating lens made of optical polymer.

Front cover: plastic. Weight: 0.45kg













Dimension



Lighting Distribution Planning Data



| H(m) | D(m) | E(lx) |
|------|------|-------|
| 1.0 | 0.51 | 2720 |
| 2.0 | 1.02 | 680 |
| 3.0 | 1.53 | 302 |
| 4.0 | 2.04 | 170 |
| 5.0 | 2.55 | 109 |
| | | |
| | | |

h=2.15m 0 3 2 [m]

ηLOR=80% . UGR=12.7

| E[lx] | 100lx | 500lx |
|--------------|-------|-------|
| a[m²] 100 | n=15 | n=74 |

All data, images, and specifications are for reference only and may be changed due to product improvement without prior notice.



3 circuit track



Surface mounted universal mono track point



Recessed mounted universal mono track point



Replaceable accessories principal lens