

## 627518.000

Technical Data Light source: LED

Wattage: 20W Voltage: 220-240VAC Nominal luminous flux: 1950lm Beam angle: 16°, spot

Color temperature: 4000K, neutral white

Color Rendering Index: 90

Technical Chracteristics

Protection degree: IP20 (En60598) Insulation class: Class I (En60598)

## Product Description


Housing and bracket: cast aluminium, powder-coated, White. 0°- 90°tilt.

Bracket rotatable through 360° on 3-circuit adapter.

3-circuit adapter: plastic.

Including electronic control, DALI Plug & Play. Replaceable LED module: high-power LEDs on metal-core PCB, Collimating lens made of optical polymer.

Front cover: plastic. Weight: 1.10kg














## Dimension



## Lighting Distribution Planning Data



H(m)	D(m)	E(lx)
1	0.26	15928
2	0.52	3982
3	0.78	1770
4	1.04	996
5	1.30	637



ηLOR=80% UGR=14.2

E[lx]	100lx	500lx
a[m²] 100	n=7	n=33

All data, images, and specifications are for reference only and may be changed due to product improvement without prior notice.



3 circuit track



Surface mounted universal mono track point



Recessed mounted universal mono track point



Replaceable accessories principal lens



Anti-glare slides



Barn door

More details at www.akzu.com/627518