


## 627531.000

Technical Data Light source: LED Wattage: 20W Voltage: 220-240VAC Nominal luminous flux: 1950lm Beam angle: 29°, flood Color temperature: 4000K, neutral white Color Rendering Index: 90

**Technical Chracteristics** Protection degree: IP20 (En60598) Insulation class: Class I (En60598)


## Product Description


Housing and bracket: cast aluminium, powder-coated, Black. 0°- 90°tilt. Bracket rotatable through 360° on 3-circuit adapter. 3-circuit adapter: plastic. Including electronic control, DALI Plug & Play. Replaceable LED module: high-power LEDs on metal-core PCB, Collimating lens made of optical polymer. Front cover: plastic. Weight: 1.10kg



☆ < € ♥ </p>

## Dimension






2 1

> 1 2

[m]

Lighting Distribution Planning Data



D(m)	E(lx)
0.51	6236
1.02	1559
1.53	693
2.04	390
2.55	249

**n**LOR=80% . UGR=13.9

H(m)

1

2 3

4 5

[lx]	100lx	500lx	
a[m² ] 100	n=7	N=33	

All data, images, and specifications are for reference only and may be changed due to product improvement without prior notice.



More details at www.akzu.com/627531

Replaceable accessories principal lens



Anti-glare slides

mono track point

Surface mounted universal



Recessed mounted universal mono track point



Barn door