
# Tracron M4 Track Lights Product Data Sheet



#### 627645.000

Technical Data Light source: LED Wattage: 20W

Voltage: 220-240VAC Nominal luminous flux: 1710lm Beam angle: 55°x19°, oval flood Color temperature: 3000K, warm white

Color Rendering Index: 95

Technical Chracteristics

Protection degree: IP20 (En60598) Insulation class: Class I (En60598)

## **Product Description**


Housing and bracket: cast aluminium, powder-coated, White. 0°- 90°tilt.

Bracket rotatable through 360° on 3-circuit adapter.

3-circuit adapter: plastic.

Including electronic control, DALI Plug & Play. Replaceable LED module: high-power LEDs on metal-core PCB, Collimating lens made of optical polymer.

Front cover: plastic. Weight: 1.10kg














#### Dimension



## Lighting Distribution Planning Data



H(m)	D(m)	D(m)	E(lx)
	CO	C90	
1	1.00	0.38	3462
2	2.00	0.76	895
3	3.00	1.14	384
4	4.01	1.53	216
5	5.01	1.91	138



ηLOR=80% UGR=14.6

E[lx]	100lx	500lx
a[m²] 100	n=8	n=37

All data, images, and specifications are for reference only and may be changed due to product improvement without prior notice.



3 circuit track



Surface mounted universal mono track point



Recessed mounted universal mono track point



Replaceable accessories principal lens



Anti-glare slides



Barn door

More details at www.akzu.com/627645