


627655.000

Technical Data Light source: LED Wattage: 20W Voltage: 220-240VAC Nominal luminous flux: 1950lm Beam angle: 55°x19°, oval flood Color temperature: 4000K, neutral white Color Rendering Index: 90

Technical Chracteristics Protection degree: IP20 (En60598) Insulation class: Class I (En60598)


Product Description


Housing and bracket: cast aluminium, powder-coated, White. 0°- 90°tilt. Bracket rotatable through 360°on 3-circuit adapter. 3-circuit adapter: plastic. Including electronic control, DALI Plug & Play. Replaceable LED module: high-power LEDs on metal-core PCB, Collimating lens made of optical polymer. Front cover: plastic. Weight: 1.10kg




☆ < € ♥ </p>

Dimension





Lighting Distribution Planning Data



D(m)	D(m)	E(Ix)
C0	C90	
1.00	0.38	3948
2.00	0.76	987
3.00	1.14	439
4.01	1.53	247
5.01	1.91	158

ηLOR=80% UGR=15.7

H(m)

1 2

3 4 5

E[lx]	100lx	500lx	
a[m²] 100	n=7	n=33	

All data, images, and specifications are for reference only and may be changed due to product improvement without prior notice. 3 circuit track Surface mounted universal mono track point Surface mounted universal



Recessed mounted universal mono track point

More details at www.akzu.com/627655



Replaceable accessories principal lens



Barn door