


601198.000

Technical Data Light source: LED Wattage: 14W Voltage: 220-240VAC Nominal luminous flux: 1140lm Beam angle: 29°, flood Color temperature: 3000K, warm white Color Rendering Index: 95

Technical Chracteristics Protection degree: IP20 (En60598) Insulation class: Class I (En60598)


Product Description

Housing and bracket: cast aluminium, powder-coated, White. 0°- 90°tilt. Bracket rotatable through 360°on 3-circuit adapter. 3-circuit adapter: plastic. Including electronic control, DALI Plug & Play. Replaceable LED module: high-power LEDs on metal-core PCB, Collimating lens made of optical polymer. Front cover: plastic. Weight: 0.70kg




☆ (€ 🗑 🏾

Dimension



60° 60° 30° 5500cd 30°

Lighting Distribution Planning Data



| D(m) | E(lx) |
|------|-------|
| 0.51 | 3645 |
| 1.02 | 911 |
| 1.53 | 405 |
| 2.04 | 227 |
| 2.55 | 145 |
| | |

ηLOR=80% UGR=10.8

H(m)

1

2 3

4 5

| E[lx] | 100lx | 500lx | |
|---------------------------|-------|-------|--|
| a[m ²] 100 | n=11 | n=55 | |

All data, images, and specifications are for reference only and may be changed due to product improvement without prior notice.



Recessed mounted universal mono track point

More details at www.akzu.com/601198



Replaceable accessories principal lens



Anti-glare slides



Barn door