

#### 601199.000

Technical Data Light source: LED Wattage: 14W

Voltage: 220-240VAC Nominal luminous flux: 1140lm Beam angle: 29°, flood

Color temperature: 3000K, warm white

Color Rendering Index: 95

### Technical Chracteristics

Protection degree: IP20 (En60598) Insulation class: Class I (En60598)

# **Product Description**


Housing and bracket: cast aluminium, powder-coated, Black. 0°- 90°tilt.

Bracket rotatable through 360° on 3-circuit adapter.

3-circuit adapter: plastic. Including electronic control, DALI Plug & Play.

Replaceable LED module: high-power LEDs on metal-core PCB, Collimating lens made of optical polymer.

Front cover: plastic. Weight: 0.70kg














#### Dimension



# Lighting Distribution Planning Data



H(m)	D(m)	E(lx)
1	0.51	3645
2	1.02	911
3	1.53	405
4	2.04	227
5	2.55	145



ηLOR=80% . UGR=10.8

E[lx]	100lx	500lx
a[m²] 100	n=11	n=55

All data, images, and specifications are for reference only and may be changed due to product improvement without prior notice.



3 circuit track



Surface mounted universal mono track point



Recessed mounted universal mono track point



Replaceable accessories principal lens



Anti-glare slides



Barn door

More details at www.akzu.com/601199