



Technical Data

Light source: LED Wattage: 14W Voltage: 220-240VAC Nominal luminous flux: 1300lm Beam angle: 47°, broad flood Color temperature: 4000K, neutral white

Color Rendering Index: 90

Technical Chracteristics

Protection degree: IP20 (En60598) Insulation class: Class I (En60598)

Product Description


Housing and bracket: cast aluminium, powder-coated, Black, 0°- 90°tilt.

Bracket rotatable through 360° on 3-circuit adapter. 3-circuit adapter: plastic.

Including electronic control, dimmable with potentiomen ter for brightness control 0-100%.

Replaceable LED module: high-power LEDs on metal-core PCB, Collimating lens made of optical polymer. Front cover: plastic.

Weight: 0.70kg













Dimension



Lighting Distribution Planning Data



H(m)	D(m)	E(lx)
1	0.88	1703
2	1.76	426
3	2.65	189
4	3.53	106
5	4.41	68

h=2.15m 0 2 3 [m]

ηLOR=80% . UGR=11.6

E[lx]	100lx	500lx
a[m²] 100	n=10	n=49

All data, images, and specifications are for reference only and may be changed due to product improvement without prior notice.



3 circuit track



Surface mounted universal mono track point



Recessed mounted universal mono track point



Replaceable accessories principal lens



Anti-glare slides



Barn door

More details at www.akzu.com/601644