


601686.000

Technical Data Light source: LED Wattage: 40W Voltage: 220-240VAC Nominal luminous flux: 3420lm Beam angle: 29°, flood Color temperature: 3000K, warm white Color Rendering Index: 95

Technical Chracteristics Protection degree: IP20 (En60598) Insulation class: Class I (En60598)


Product Description

Housing and bracket: cast aluminium, powder-coated, Black. 0°- 90°tilt. Bracket rotatable through 360° on 3-circuit adapter. 3-circuit adapter: plastic. Including electronic control, DALI Plug & Play. Replaceable LED module: high-power LEDs on metal-core PCB, Collimating lens made of optical polymer. Front cover: plastic. Weight: 1.60kg




☆ < € < ▼ </p>

Dimension



60° 60 30° 30 14000cd

Lighting Distribution Planning Data



D(m)	E(Ix)
1.02	2736
2.04	684
3.06	304
4.08	171
5.10	109

nLOR=80% . UGR=12.7

H(m)

2

4 6

8 10

E[lx]	100lx	500lx	
a[m²] 100	n=4	n=19	

All data, images, and specifications are for reference only and may be changed due to product improvement without prior notice.







Surface mounted universal mono track point



Recessed mounted universal mono track point

More details at www.akzu.com/601686



Replaceable accessories

Anti-glare slides

Barn door