


601689.000

Technical Data Light source: LED Wattage: 40W Voltage: 220-240VAC Nominal luminous flux: 3420lm Beam angle: 29°, flood Color temperature: 3000K, warm white Color Rendering Index: 95

Technical Chracteristics Protection degree: IP20 (En60598) Insulation class: Class I (En60598)


Product Description

Housing and bracket: cast aluminium, powder-coated, Black, 0°- 90°tilt. Bracket rotatable through 360° on 3-circuit adapter. 3-circuit adapter: plastic. Including electronic control, dimmable with potentiomen ter for brightness control 0-100%. Replaceable LED module: high-power LEDs on metal-core PCB, Collimating lens made of optical polymer. Front cover: plastic. Weight: 1.60kg




Dimension

Lighting Distribution Planning Data



60° 60 30° 30 14000cd



D(m)	E(lx)
1.02	2736
2.04	684
3.06	304
4.08	171
5.10	109

nLOR=80% . UGR=12.7

H(m)

2

4 6

8 10

E[lx]	100lx	500lx	
a[m²] 100	n=4	n=19	

All data, images, and specifications are for reference only and may be changed due to product improvement without prior notice.







Surface mounted universal mono track point



Recessed mounted universal mono track point

More details at www.akzu.com/601689

Replaceable accessories principal lens



Anti-glare slides



Barn door