


601723.000

Technical Data Light source: LED Wattage: 40W Voltage: 220-240VAC Nominal luminous flux: 3900lm Beam angle: 16°, spot Color temperature: 4000K, neutral white Color Rendering Index: 90

Technical Chracteristics Protection degree: IP20 (En60598) Insulation class: Class I (En60598)


Product Description


Housing and bracket: cast aluminium, powder-coated, White. 0°- 90° tilt. Bracket rotatable through 360° on 3-circuit adapter. 3-circuit adapter: plastic. Including electronic control, DALI Plug & Play. Replaceable LED module: high-power LEDs on metal-core PCB, Collimating lens made of optical polymer. Front cover: plastic. Weight: 1.60kg




☆ < € < ▼ </p>

Dimension





Lighting Distribution Planning Data



D(m)	E(lx)
0.52	7957
1.04	1989
1.56	884
2.08	497
2.60	318

ηLOR=80% . UGR=12.3

H(m)

2

4 6

8 10

E[lx]	100lx	500lx
a[m ²] 100	n=4	n=16

All data, images, and specifications are for reference only and may be changed due to product improvement



without prior notice.

More details at www.akzu.com/601723





mono track point

Anti-glare slides

Surface mounted universal



Recessed mounted universal mono track point



Barn door