


601726.000

Technical Data Light source: LED Wattage: 40W Voltage: 220-240VAC Nominal luminous flux: 3900lm Beam angle: 16°, spot Color temperature: 4000K, neutral white Color Rendering Index: 90

Technical Chracteristics Protection degree: IP20 (En60598) Insulation class: Class I (En60598)

Product Description


Housing and bracket: cast aluminium, powder-coated, White, 0°- 90°tilt. Bracket rotatable through 360°on 3-circuit adapter. 3-circuit adapter: plastic. Including electronic control, dimmable with potentiomen ter for brightness control 0-100%. Replaceable LED module: high-power LEDs on metal-core PCB, Collimating lens made of optical polymer. Front cover: plastic. Weight: 1.60kg





Dimension

Lighting Distribution Planning Data

☆ < € ♥ </p>







D(m)	E(lx)
0.52	7957
1.04	1989
1.56	884
2.08	497
2.60	318

ηLOR=80% . UGR=12.3

H(m)

2

4 6

8 10

500lx 100lx E[lx] n=4 n=16 a[m²] 100

All data, images, and specifications



are for reference only and may be changed due to product improvement without prior notice.

More details at www.akzu.com/601726



Replaceable accessories



Surface mounted universal mono track point

Anti-glare slides



Recessed mounted universal mono track point



Barn door