
Tracron M6 Track Lights Product Data Sheet





601727.000

Technical Data Light source: LED Wattage: 40W

Color temperature: 4000K, neutral white

Color Rendering Index: 90

Voltage: 220-240VAC Nominal luminous flux: 3900lm

Technical Chracteristics

Protection degree: IP20 (En60598) Insulation class: Class I (En60598)

Product Description


Housing and bracket: cast aluminium, powder-coated, Black, 0°- 90°tilt.

Bracket rotatable through 360° on 3-circuit adapter. 3-circuit adapter: plastic.

Including electronic control, dimmable with potentiomen ter for brightness control 0-100%.

Replaceable LED module: high-power LEDs on metal-core PCB, Collimating lens made of optical polymer. Front cover: plastic.

Weight: 1.60kg













Dimension



Lighting Distribution Planning Data



| | 2 | | | h= | =2.15m | |
|-----|---|-----|--------|-----|----------------|---|
| | Z | | | | | |
| | 1 | | | | | |
| | 0 | 50 | 29/5.9 | | | |
| | 1 | 4 | 2.0 | | | |
| | 2 | | | | | |
| [m] | | 1 (| 0 - | 1 2 | 2 3 | 3 |

H(m) E(lx)D(m) 7957 0.52

4 1989 1.04 1.56 884 6 2.08 497 10 2.60 318

ηLOR=80% UGR=12.3

| E[lx] | 100lx | 500lx | |
|-------|-------|-------|--|
| a[m²] | n=4 | n=16 | |
| 100 | | | |

All data, images, and specifications are for reference only and may be changed due to product improvement without prior notice.



3 circuit track

principal lens

Replaceable accessories



Surface mounted universal mono track point



Recessed mounted universal mono track point





Barn door

More details at www.akzu.com/601727