
# Tracron M6 Track Lights Product Data Sheet











#### 601738.000

Technical Data Light source: LED Wattage: 40W Voltage: 220-240VAC Nominal luminous flux: 3900lm

Beam angle: 29°, flood

Color temperature: 4000K, neutral white

Color Rendering Index: 90

#### Technical Chracteristics

Protection degree: IP20 (En60598) Insulation class: Class I (En60598)

### Product Description


Housing and bracket: cast aluminium, powder-coated, White, 0°- 90°tilt.

Bracket rotatable through 360° on 3-circuit adapter. 3-circuit adapter: plastic.


Including electronic control, dimmable with potentiomen ter for brightness control 0-100%.

Replaceable LED module: high-power LEDs on metal-core PCB, Collimating lens made of optical polymer. Front cover: plastic.


Weight: 1.60kg



## Dimension



### Lighting Distribution Planning Data



	2			h=	ı =2.15m I	
	1					
	0	50_	20,5 d			
	1	10	<b>2.0</b> -			
	2					
[m]	_	1 (	0 -	1 2	2 3	3

H(m) D(m) E(lx)

2	1.02	3120
4	2.04	780
6	3.06	347
8	4.08	195
10	5.10	125

ηLOR=80% UGR=13.9

E[lx]	100lx	500lx
a[m²]	n=4	n=16
100		

All data, images, and specifications are for reference only and may be changed due to product improvement without prior notice.



3 circuit track



Surface mounted universal mono track point



Recessed mounted universal mono track point





Replaceable accessories principal lens



Anti-glare slides



Barn door