



SISTEM EVO 2 FRAME MATT WHITE

LL-9102-W


MATT WHITE

IP20

HOLE SIZE: 185x90mm RECTANGLE

The Sistem Evo 2 is a new generation of architectural downlight utilising leading-edge technology. With an easy snap-in insert which houses the entire Hero LED engine range allowing for efficient installation and maintenance, function is at the forefront. The Sistem Evo defines simple design at its best, employing a subtle curved form with adjustability for directional combinations.

* To make a complete fitting you need to order both the frame and 2x inserts - LL-9100-B or LL-9100-W



* Height with Hero Pro II

Components						
LL-9100-B	SISTEM EVO INSERT MATT BLACK					
LL-9100-W	SISTEM EVO INSERT MATT WHITE					

Light Source						
LL-010-27-40	HERO ECO 9W 40D 27K CRI >90	9W	2700°K	40°	Ra90	500mA
LL-010-30-40	HERO ECO 9W 40D 30K CRI >90	9W	3000°K	40°	Ra90	500mA
LL-010-40-40	HERO ECO 9W 40D 40K CRI >90	9W	4000°K	40°	Ra90	500mA
LL-010-27-60	HERO ECO 9W 60D 27K CRI >90	9W	2700°K	60°	Ra90	500mA
LL-010-30-60	HERO ECO 9W 60D 30K CRI >90	9W	3000°K	60°	Ra90	500mA
LL-010-40-60	HERO ECO 9W 60D 40K CRI >90	9W	4000°K	60°	Ra90	500mA
LL-040-27-18	HERO XP 9W 18D 27K CRI90	9W	2700°K	18° 1110lm	Ra90	250mA
LL-040-27-24	HERO XP 9W 24D 27K CRI90	9W	2700°K	24° 1110lm	Ra90	250mA
LL-040-27-36	HERO XP 9W 36D 27K CRI90	9W	2700°K	36° 1110lm	Ra90	250mA
LL-040-27-60	HERO XP 9W 60D 27K CRI90	9W	2700°K	60° 1110lm	Ra90	250mA
LL-040-30-18	HERO XP 9W 18D 30K CRI90	9W	3000°K	18° 1140lm	Ra90	250mA
LL-040-30-24	HERO XP 9W 24D 30K CRI90	9W	3000°K	24° 1140lm	Ra90	250mA
LL-040-30-36	HERO XP 9W 36D 30K CRI90	9W	3000°K	36° 1140lm	Ra90	250mA
LL-040-30-60	HERO XP 9W 60D 30K CRI90	9W	3000°K	60° 1140lm	Ra90	250mA
LL-040-40-18	HERO XP 9W 18D 40K CRI90	9W	4000°K	18° 1220lm	Ra90	250mA
LL-040-40-24	HERO XP 9W 24D 40K CRI90	9W	4000°K	24° 1220lm	Ra90	250mA
LL-040-40-36	HERO XP 9W 36D 40K CRI90	9W	4000°K	36° 1220lm	Ra90	250mA
LL-040-40-60	HERO XP 9W 60D 40K CRI90	9W	4000°K	60° 1220lm	Ra90	250mA
LL-050-27-18	HERO XP 12W 18D 27K CRI90	12W	2700°K	18° 1470lm	Ra90	350mA
LL-050-27-24	HERO XP 12W 24D 27K CRI90	12W	2700°K	24° 1470lm	Ra90	350mA
LL-050-27-36	HERO XP 12W 36D 27K CRI90	12W	2700°K	36° 1470lm	Ra90	350mA
LL-050-27-60	HERO XP 12W 60D 27K CRI90	12W	2700°K	60° 1470lm	Ra90	350mA
LL-050-30-18	HERO XP 12W 18D 30K CRI90	12W	3000°K	18° 1520lm	Ra90	350mA
LL-050-30-24	HERO XP 12W 24D 30K CRI90	12W	3000°K	24° 1520lm	Ra90	350mA
LL-050-30-36	HERO XP 12W 36D 30K CRI90	12W	3000°K	36° 1520lm	Ra90	350mA
LL-050-30-60	HERO XP 12W 60D 30K CRI90	12W	3000°K	60° 1520lm	Ra90	350mA
LL-050-40-18	HERO XP 12W 18D 40K CRI90	12W	4000°K	18° 1570lm	Ra90	350mA
LL-050-40-24	HERO XP 12W 24D 40K CRI90	12W	4000°K	24° 1570lm	Ra90	350mA
LL-050-40-36	HERO XP 12W 36D 40K CRI90	12W	4000°K	36° 1570lm	Ra90	350mA
LL-050-40-60	HERO XP 12W 60D 40K CRI90	12W	4000°K	60° 1570lm	Ra90	350mA
LL-060-27-18	SUPERHERO XP 18W 18D 27K CRI90	18W	2700°K	18° 2110lm	Ra90	500mA
LL-060-27-24	SUPERHERO XP 18W 24D 27K CRI90	18W	2700°K	24° 2110lm	Ra90	500mA
LL-060-27-36	SUPERHERO XP 18W 36D 27K CRI90	18W	2700°K	36° 2110lm	Ra90	500mA
LL-060-27-60	SUPERHERO XP 18W 60D 27K CRI90	18W	2700°K	60° 2110lm	Ra90	500mA
LL-060-30-18	SUPERHERO XP 18W 18D 30K CRI90	18W	3000°K	18° 2180lm	Ra90	500mA
LL-060-30-24	SUPERHERO XP 18W 24D 30K CRI90	18W	3000°K	24° 2180lm	Ra90	500mA
LL-060-30-36	SUPERHERO XP 18W 36D 30K CRI90	18W	3000°K	36° 2180lm	Ra90	500mA
LL-060-30-60	SUPERHERO XP 18W 60D 30K CRI90	18W	3000°K	60° 2180lm	Ra90	500mA
LL-060-40-18	SUPERHERO XP 18W 18D 40K CRI90	18W	4000°K	18° 2400lm	Ra90	500mA

LL-060-40-24	SUPERHERO XP 18W 24D 40K CRI90	18W	4000°K	24°	2400lm	Ra90	500mA
LL-060-40-36	SUPERHERO XP 18W 36D 40K CRI90	18W	4000°K	36°	2400lm	Ra90	500mA
LL-060-40-60	SUPERHERO XP 18W 60D 40K CRI90	18W	4000°K	60°	2400lm	Ra90	500mA